

17/235, 21/215 Technical Specifications





Model			17/235	21/215
Performance	Rated operating pressure	bar (psig)	17.2 (250)	21.0 (300)
	Free air delivery	m³/min (cfm)*	23.4 (825)	21.5 (760)
	Maximum operating pressure	bar (psig)	21.0 (300)	24.1 (350)
Engine	Make		Caterpillar	Caterpillar
	Model		3306 ATAAC	3306 ATAAC
	Power	kW (BHP)	250 (340)	250 (340)
	Number of cylinders		6	6
	Speed	rpm	1800	1800
Dimensions	Overall length	(A) - m	4.21	4.21
	Overall width	(B) - m	2.00	2.00
	Overall height	(C) - m	2.22	2.22
	Track width	(D) - m	1.65	1.65
	Ground clearance	(E) - m	0.30	0.30
	Weight - nett	kg	4151	4151
	Weight - Gross	kg	4670	4670
	Fuel tank capacity	litres	600	600
	Air outlets	BSPT	1 x 2", 3 x 1 ¹ / ₄ "	1 x 2", 3 x 1 ¹ / ₄ "
	Tyre size		750 x 16 x 6PR	750 x 16 x 6PR

^{*} Tested to ISO 1217:1996

Ingersoll-Rand European Sales Limited Swan Lane, Wigan WN2 4EZ United Kingdom Tel: 01942 257171 Telex: 67420 Fax: 01942 523417

Nothing contained within this brochure is intended to extend any warranty or representation, expressed or implied, regarding the products described herein. Any such warranties or other terms or conditions of sale of products shall be in accordance with Ingersoll-Rand Standard Terms and Conditions of Sale for such products, which are available upon request. The manufacturer reserves the right to change or delete models and/or specifications without prior notice.



